

LINE Resellers

Sheet No. 43.111

Rev. 2

Year August 2013

PRODUCT ATRIAFLOOR CERA

Type of Product

Self-polishing and scratch-resistant water-based wax.

Atriafloor Wax is a self-polishing and scratch resistant water-based liquid compound. Specially formulated to protect Atriafloor floors, makes the treated surface even, improving the aesthetic impact of the work. Available in glossy version, Atriafloor Wax helps to prolong the life of the floor and helps in the daily maintenance ensuring exceptional results.

Fields of Application

For surfaces with Atriafloor coating or epoxy coating.

Technical Characteristics	Appearance	Liquid, perfumed
	Colour	Milky white
	Flash point	Not flammable
	PH	7
	Specific weight	1,000g/ml
	Toxicity	Not toxic - Not harmful
	ADR	no
	VOC (direttiva 199/13/ CE)	0
	VOC (carbonio volatile)	0
	Dilution	Water
	Washing tools	Water
	Theoretical spreadin	30 - 40 gr./m ²
	APPLICATION METHOD	
	Cloth	Pure 1st coat
	Spreader	Pure 1st coat
	Working temperature	above 15°C - low humidity rate
	DRYING 25°C	
	Dry in Depth	2 - 4 hours
	Cold resistance	Until -30°C tested
	Storage stability	12 months at a temperature above 10°C
	Standard packages	Lt 0,750

Notes

The product must be tightly closed when stored and at temperatures no lower than 10°C and no greater than 35°C.; strictly avoid open containers from being exposed to air and moisture. Climatic conditions affect the hardening and chemical and mechanical resistance of the finished product, we recommend heating the room during cold and humid seasons.

LINE Resellers
Sheet No. 43.111
Rev. 2
Year 2013



PRODUCT ATRIAFLOOR CERA

Rules of Application Surface Preparation

Well cleaned free of dust and oil contaminants. Thoroughly clean using a soft cloth and warm water before applying the product. Wait for the surface to dry completely before applying the wax (about 4 hours).

Application method

Apply a pure coat at temperatures exceeding 15°C. with a soft cloth or spreader. Close the windows to prevent the product from drying too quickly as this may cause surface stains or overlap problems. Periodically apply the wax by diluting the product to 50% more on floors clean and dry.

Cleaning

For cleaning, we recommend using a soft cloth with neutral detergent that does not leave marks or polishing.

Maintenance

In case of scratches or wear of the floor, sand the surface with 500/1000 type sandpaper, then apply Atriafloor Protettivo Transparent.

Recommended for Protection and maintenance of the Atriafloor system

Not recommended for Outdoor flooring

Recommended Finishes Not applicable

Safety information PROTECT FROM FROST. The product does not require any special precautions.

Keep out of reach of children. Avoid contact with eyes and skin. In the event of contact with eyes, rinse with plenty of water and seek medical advice. If swallowed, induce vomiting and seek medical advice. Apply according to good work hygiene

standards.

For more information, refer to the corresponding safety data sheet.

^(*) This information, despite being deemed reliable, must be regarded as indicative, the company reserves the right to change it without notice. The use of this information does not imply any responsibility on our part, including the violation of any license. It is the users' responsibility to check the suitability of the product for the specific use in advance. For further clarification or specific questions regarding products please contact the technical laboratory manager.