



|           |             |
|-----------|-------------|
| LINE      | Resellers   |
| Sheet No. | 90.107      |
| Rev.      | 5           |
| Year      | August 2013 |



PRODUCT **ATRIAFLOOR PRIMER**

**Rules of Application**

**Surface Preparation**

- **Painted iron:** thoroughly cleaned, sand well and remove all loose parts; recover areas where the metal is bare with a suitable primer (PRIMEPOX, Protex) and apply one or two coats of **Atriafloor Primer**.
- **New wood or MDF:** thoroughly cleaned and sanded, apply a first coat of **Atriafloor Primer** diluted to 20% with water.
- **Ceramic surfaces:** thoroughly cleaned and dusted apply a first coat of **Atriafloor Primer** . After drying, if necessary grout the joints with Atriafloor Stucco to even out the surface, the excess grout must be sanded.

**Recommended for**

Cycles resistant to chemical products- continuous immersion and as a promoter of non-toxic coatings for food containers.

**Not recommended for**

Direct exposure to sunlight; acids; concentrated bases; solvents. Avoid surfaces with rising damp. **Not suitable for marble surfaces.**

**Recommended Finishes**

Atriafloor System Decorations.

**Safety information**

The product is not flammable.  
 For the application, observe the rules of hygiene required by the current regulations.  
 Do not dispose of the product or container in the environment.  
 For more information, refer to the corresponding technical safety data sheet.

(\*) This information, despite being deemed reliable, must be regarded as indicative, the company reserves the right to change it without notice. The use of this information does not imply any responsibility on our part, including the violation of any license. It is the users' responsibility to check the suitability of the product for the specific use in advance. For further clarification or specific questions regarding products please contact the technical laboratory manager.